

R-528 SPECIFICATIONS

Type:	Passive Radiator, front-firing active woofer, down-firing passive radiator
Active Drive Unit:	12 in., 300mm long-throw, steel chassis
Passive Radiator:	12 in., 300mm
Lower Frequency Response in Room:	21Hz at -6 dB
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Gain Control Range:	80 dB
Power Output:	500 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class D
Protection System	
Fully Electronic with SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	5 Amp semi delay 230 volts operation 9 Amp semi delay 115 volts operation
Dimensions (WHD), Including Feet:	15.5 x 17.5 x 17.2 in., (394 x 445 x 436 mm)
Net Weight:	58 lbs. (26.3 kg) Finish Gloss Piano Black Lacquer
Supplied Accessories	
Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

In the interest of product development, REL acoustics Limited reserve the right to vary these specifications without notice.