

T-5 SPECIFICATIONS

Type:	Closed Box, down-firing active woofer
Active Drive Unit:	8in., 200 mm long-throw, steel chassis
Lower Frequency Response:	32 Hz at -6 dB in room
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Input Impedance: High Level:	150k, Low Level: 10k, .1/LFE: 10k ohms
Gain Control	Range: 80 dB
Power Output:	125 Watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class AB

Protective System

Fully Electronic SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	1.6 Amp semi delay 230 volts operation, 3.15 Amp semi delay 115 volts operation
Dimensions (WHD) Including Feet:	10.5 x 11.75 x 11.75 in., (266.7 x 298.4 x 298.4 mm)
Net Weight:	26 lbs. (11.7 kg)
Finish:	Gloss Piano Black or White Lacquer

Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

In the interest of product improvement, REL Acoustics Limited reserves the right to alter these specifications without notice.