

## T-9 SPECIFICATIONS

Type:	Passive Radiator, front-firing passive radiator, down-firing active woofer
Active Drive Unit:	10in., 254 mm long-throw, steel chassis
Passive Radiator:	10in., 254 mm
Lower Frequency Response:	28 Hz at -6 dB in room
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Input Impedance: High Level:	150k, Low Level: 10k, .1/LFE: 10k ohms
Gain Control Range:	80 dB
Power Output:	300 Watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class AB

### Protection System

Fully Electronic SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	3.15 Amp semi delay 230 volts operation, 6.3 Amp semi delay 115 volts operation
<b>Dimensions</b> (WHD), Including Feet:	13 x 14.75 x 14.75 in., (330 x 374.6 x 374.6 mm)
Net Weight:	39 lbs. (17.7 kg)
Finish:	Gloss Piano Black or White Lacquer
Supplied Accessories	
Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

*In the interest of product development, REL acoustics Limited reserve the right to vary these specifications without notice.*