

R-328 specifications

Type:	Passive Radiator, front-firing active woofer, down-firing passive radiator
Active Drive Unit:	10 in., 250mm long-throw, steel chassis
Passive Radiator:	12 in., 300mm
Lower Frequency Response in Room:	22Hz at -6 dB
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Gain Control Range:	80 dB
Power Output:	350 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class D

Protection System

Fully Electronic with SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	4 Amp semi delay 230 volts operation 8 Amp semi delay 115 volts operation

Dimensions (WHD), Including Feet:

Net Weight:	13.5 x 15.1 x 15.2 in., (343 x 384 x 385 mm) 45 lbs. (20.4 kg)
Finish:	Gloss Piano Black Lacquer

Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

In the interest of product development, REL acoustics Limited reserve the right to vary these specifications without notice.

