

## R-218 specifications

Type:	Down-firing active woofer
Active Drive Unit:	10 in., 250mm long-throw, steel chassis
Lower Frequency Response in Room:	25Hz at -6 dB
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Gain Control Range:	80 dB
Power Output:	250 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class D
<b>Protection System</b>	
Fully Electronic with SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Mains Fuse:	3.15 Amp semi delay 230 volts operation 6.3 Amp semi delay 115 volts operation
<b>Dimensions</b> (WHD), Including Feet:	12 x 13.6 x 12.5 in., (305 x 346 x 318 mm)
Net Weight:	29 lbs. (13.2 kg)
Finish:	Gloss Piano Black or White Lacquer
<b>Supplied Accessories</b>	
Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

*In the interest of product development, REL acoustics Limited reserve the right to vary these specifications without notice.*