

## G-2 SPECIFICATIONS

|                                   |  |
|-----------------------------------|--|
| Type:                             | Closed box, front firing woofer  |
| Drive Unit:                       | 10 in., 250mm long throw, carbon fiber cone                            |
| Lower Frequency Response in Room: | -6dB at 18Hz   |
| Input Connectors:                 | High-Level Neutrik Speakon, Low-Level stereo phono, LFE phono, LFE XLR |
| Output Connectors:                | High-Level Neutrik Speakon, LFE phono, LFE XLR                         |
| Gain Control Range:               | 80 dB  |
| Power Output:                     | 450 Watts (RMS) Ultra High-Current Power Supply                        |
| Phase Switch:                     | Yes, 0 or 180 degrees  |
| Amplifier Type:                   | Class AB   |

### Protection System

|                                 |   |
|---------------------------------|---|
| Fully Electronic with SET-SAFE: | Yes   |
| DC Fault:                       | Yes   |
| Output Short:                   | Yes   |
| Mains Input Voltage:            | 220-240 volts, 110-120 volts for certain markets                              |
| Mains Fuse:                     | 5 Amp semi delay 230 volts operation<br>10 Amp semi delay 115 volts operation |

|  |  |
|--|--|
| <b>Dimensions</b> (WHD), Including Feet: | 20 x 16.4 x 24 in., (508.8 x 417.3 x 610.4 mm) |
| Net Weight:                              | 84lbs. (38.1kg)                                |

### Supplied Accessories

|                               |                         |
|-------------------------------|-------------------------|
| Mains Lead:                   | Yes                     |
| Neutrik Speakon Interconnect: | Yes (10 Meters Nominal) |
| Users Manual:                 | Yes                     |
| Remote Control:               | Yes                     |
| Batteries (AAA x 2):          | Yes                     |
| Spikes (x 4):                 | Yes                     |
| Allen Key (2.5mm):            | Yes                     |

*In the interest of product development, REL Acoustics Limited reserve the right to vary these specifications without notice.*