

G-1 SPECIFICATIONS

Type:	Closed box, front firing woofer
Drive Unit:	12 in., 300mm long throw, carbon fiber cone
Lower Frequency Response in Room:	-6dB at 15Hz
Input Connectors:	High-Level Neutrik Speakon, Low-Level stereo phono, LFE phono, LFE XLR
Output Connectors:	High-Level Neutrik Speakon, LFE phono, LFE XLR
Gain Control Range:	80 dB
Power Output:	600 WATTS (RMS) Ultra High-Current Power Supply
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class AB
Protection System	
Fully Electronic with SET-SAFE:	Yes
DC Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Mains Fuse:	5 Amp semi delay 230 volts operation 10 Amp semi delay 115 volts operation
Dimensions (WHD), Including Feet:	22.5 x 18.2 x 26.8 in., (571.5 x 462 x 680.3 mm)
Net Weight:	108 lbs. (49 kg)
Supplied Accessories	
Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes
Remote Control:	Yes
batteries (AAA x 2):	Yes
Spikes (x 4):	Yes
Allen Key (2.5mm):	Yes

In the interest of product development, REL acoustics Limited reserve the right to vary these specifications without notice.