

REL

ACOUSTICS
• LTD •

T/7i Specifications

Type:	Passive Radiator, front-firing active woofer, down-firing passive radiator
Active Drive Unit:	8in., 200 mm long-throw, inverted dust cap, steel chassis
Passive Radiator:	10in., 254 mm
Lower Frequency Response:	30 Hz at -6 dB in room
Input Connectors:	Hi Level Neutrik Speakon, Lo Level single phono, LFE phono
Input Impedance:	High Level: 150k, Low Level: 10k, .1/LFE: 10k ohms
Gain Control Range:	80 dB
Power Output:	200 Watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class AB

Protection System

Fully Electronic SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses:	2 Amp semi delay 230 volts operation, 4 Amp semi delay 115 volts operation
Dimensions (WHD):	12 x 14.3 x 15 in., (305 x 362 x 382 mm) Including Feet and Rear Panel Controls Add 1.75 in (44.5 mm) in depth when using Hi Level connector
Net Weight:	36 lbs. (16.3 kg)
Finish:	Gloss Piano Black or White Lacquer

Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (10 Meters Nominal)
Users Manual:	Yes

In the interest of product development, REL Acoustics Limited reserves the right to vary these specifications without notice.