

T-ZERO SPECIFICATIONS

| | |
|---------------------------|---|
| Type: | Sealed, down-firing active woofer |
| Drive Unit: | 6.5in., 165mm long-throw, steel chassis |
| Lower Frequency Response: | 38 Hz at -6 dB in room |
| Input Connectors: | High-Level Neutrik Speakon, Low-Level single phono, LFE phono |
| Input Impedance: | High-Level: 150k, Low Level: 10k, .1/LFE: 10k ohms |
| Gain Control Range: | 80 dB |
| Power Output: | 100 Watts (RMS) |
| Phase Switch: | Yes, 0 or 180 degrees |
| Amplifier Type: | Class D |

Protection System

| | |
|----------------------------|--|
| Fully Electronic SET-SAFE: | Yes |
| D.C. Fault: | Yes |
| Output Short: | Yes |
| Mains Input Voltage: | 100-240 volts |
| Fuse: | 2.00 Amp semi delay |
| Dimensions (WHD): | 8.5 x 9.5 x 10.25 in., (216 x 241 x 260 mm) Including Feet |
| Net Weight: | 15 lbs. (6.8 kg) |
| Finish: | Gloss Piano Black or White Lacquer |

Supplied Accessories

| | |
|-------------------------------|-------------------------|
| Mains Lead: | Yes |
| Neutrik Speakon Interconnect: | Yes (10 Meters Nominal) |
| User Manual: | Yes |

In the interest of product improvement, REL Acoustics Limited reserves the right to alter these specifications without notice.