

## Specifications

Type:	S/3
Active Drive Unit:	Front-firing active woofer, down-firing passive radiator
Passive Radiator:	10 in., 250mm long-throw, pressed Aluminium chassis
Lower Frequency Response in Room:	12 in., 300mm
Input Connectors:	22Hz at -6 dB
	Hi Level Neutrik Speakon,
	Left and Right Lo Level phono,
	LFE phono, SMA for wireless antenna
Gain Control Range:	80 dB
Power Output:	400 watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Next Gen II Class D
REL Longbow Wireless capability:	Yes – REL Longbow™ transmitter [required], Sold separately

## Protection System

Fully Electronic with SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	220-240 volts, 110-120 volts for certain markets
Fuses (semi delay):	5 Amp 220 volts operation 9 Amp 120 volts operation
Dimensions (W x H x D)*:	16 x 16.7 x 18.25 in., (406 x 424 x 463.5 mm)
Net Weight:	61.4 lbs. (27.85 kg)
Shipping Weight:	71 lbs. (32.2 kg)
Finish (Gloss):	Piano Black White Lacquer

## Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon Interconnect 10 Metres Nominal:	Yes

\* Including Feet and Rear Panel Controls, Add 1.75in (44.5mm) in depth when using Hi Level connector

*In the interest of product development, REL Acoustics Limited reserve the right to vary these specifications without notice.*