

Habitat 1 Specifications

Type:	Sealed, two front-firing active woofers, one back-firing passive woofer
Drive Unit:	Two 6.5 in., 165 mm long-throw, steel chassis
Passive Unit:	10 in, steel chassis
Lower Frequency Response:	30Hz at -6dB in room
Input Connectors:	High-Level Neutrik Speakon Low-Level single phono LFE single phono
Input Impedance	
High-Level:	150k
Low-Level:	10k
.1/LFE:	10k ohms
Gain Control Range:	80dB
Power Output:	150 Watts (RMS)
Phase Switch:	Yes, 0 or 180 degrees
Amplifier Type:	Class D

Protection System

Fully Electronic

SET-SAFE:	Yes
D.C. Fault:	Yes
Output Short:	Yes
Mains Input Voltage:	100-240V
Fuse:	1.6A for 230V operation 3.16A for 120V operation
Power Consumption:	16.3 Watts for 120V operation 19 Watts for 230V operation When mains switch is turned off, unit draws no power
Dimensions (WHD):	25 x 16 x 4.5 in., (635 x 406 x 114 mm)
Net Weight:	50lbs. (23kg)
Finish:	Gloss Piano Black or Gloss White Lacquer

Supplied Accessories

Mains Lead:	Yes
Neutrik Speakon Interconnect:	Yes (2 meter cable intended for use with Longbow™ transmitter)
User Manual:	Yes

Longbow™ Transmitter

Input Connectors:	High-Level Neutrik Speakon Low-Level single phono LFE single phono
Input Impedance:	
High-Level:	150k
Low Level:	10k
.1/LFE:	10k ohms
Wireless Output Power:	11dBm
Wireless Effective Distance:	50 ft (15.2 meters) with clear line of site 30 ft (9.1 meters) with single stud wall between transmitter and receiver
Mains Input Voltage:	9V DC, 5.5 mm circular connector, positive center
Power Consumption:	600 mW
Dimensions (WHD):	6 x 2 x 6.5 in., (152.4 x 50.8 x 165 mm)
Finish:	Gloss Piano Black or Gloss White Lacquer

Supplied Accessories

Power Adaptor:	Yes
----------------	-----

In the interest of product improvement, REL Acoustics Limited reserves the right to alter these specifications without notice.