

### **G-1 Mk II Specifications**

Type: Closed box, front firing woofer  
Drive Unit: 12 in., 300mm long throw, carbon fiber cone with inverted carbon fibre centre cap.  
Lower Frequency Response in Room: -6dB at 15Hz  
Input Connectors: High Level Neutrik Speakon, Low Level stereo RCA, LFE RCA  
Gain Control Range: 80 dB  
Power Output: 600 Watts (RMS) Ultra High-Current Power Supply  
Phase Switch: Yes, 0 or 180 degrees  
Amplifier Type: Class AB  
Protection System  
Fully Electronic with SET-SAFE: Yes  
DC Fault: Yes  
Output Short: Yes  
Mains Input Voltage: 220-240 volts, 110-120 volts for certain markets  
Fuses: 5 Amp semi delay 230 volts operation  
10 Amp semi delay 115 volts operation  
Dimensions  
W x H x D, Inc. Feet: 22.5 x 18.2 x 26.8 in., (571.5 x 462 x 680.3 mm)  
Net Weight: 108 lbs. (49 kg)  
Supplied Accessories  
Mains Lead: Yes  
Neutrik Speakon Interconnect 10 Meters Nominal: Yes  
Users Manual: Yes  
Remote Control: Yes  
Batteries (AAA x 2): Yes  
Spikes (x 4): Yes  
Allen Key (2.5mm): Yes