

212/SX

212/SX builds on the strengths of the legendary 212/SE. Upgraded alloy drivers with carbon fiber blades are stronger, a new flat passive radiator extends even deeper and our PerfectFilter™ delivers crushing low bass with greater speed and air, taking 212/SX well beyond its illustrious predecessor.

At REL, a deeper understanding of quality underpins everything we do. So, whilst 212/SX thunders and shakes foundations, it also resolves detail and restores midrange warmth to its correct balance. At 1,000 watts with (4) 12" (350mm) drivers, 212/SX drives rooms hard and in multiple modes which allows it to create richer bass everywhere in a room.

Refinements to both our legendary ultra-fast filters and newly developed drivers produces harder slam and brings to life quieter, gentler moments, improving system performance at both extremes. Plays brilliantly with both high end 2-channel and large power theatre applications.

SPECIFICATIONS

TYPE	(2) Front-firing active drivers, (1) rear passive, (1) down-firing passive
ACTIVE DRIVER SIZE & MATERIAL	(2) 12 in., 300mm long-throw, Continuous CastAlloy™ cone structure, cast chassis
PASSIVE RADIATOR SIZE & MATERIAL	(2) 12 in., 300mm Carbon/Carbon flat cone structure, steel chassis
LOW FREQUENCY EXTENSION	-6dB at 18 Hz
INPUT CONNECTORS	High Level Neutrik Speakon, Low Level stereo RCA, LFE RCA, SMA for wireless antenna
OUTPUT CONNECTORS	High Level, LFE RCA and LFE XLR
POWER OUTPUT	1,000 watts (RMS)
AMPLIFIER TYPE	NextGen5 Class D
WIRELESS CAPABILITY	Yes, REL AirShip system [required]. Sold separately.
WxHxD, INCLUDING FEET & REAR PANEL CONTROLS	14 1/4in., x 33in., x 20 1/4 in., (362 x 838 x 514.5mm)
NET WEIGHT	128 lbs. (58 kg)
FINISH	Piano Black Lacquer 8 coats

All RELs - Fully Electronic SET-SAFE, output short, DC Fault

